

TL (Physical Pixel Technology) SPORT PRODUCTS – January 2009

This product's list cancels and replaces any previous release. In order to improve products and technology continuously and meet the requirements of an ever evolving marketplace, the manufacturer reserves the right to modify the below contents at any moment without prior notice.

MODEL	TL4	TL6	TL10	TL12
<i>Use</i>	Indoor	Indoor	Outdoor	Outdoor
<i>LEDs per Pixel</i>	1 RGB (SMD)	1 RGB (SMD)	1 RGB (SMD)	1 RGB (SMD)
<i>Physical Pitch – mm</i>	4	6	10	12,5
<i>Panel Size - mm</i>	576x384	576x384	640x480	800x600
<i>Tile Size – mm</i>	192x192	192x96	160x160	200x200
<i>Physical Tile Graphic Definition - Px</i>	48x48	32x16	16x16	16x16
<i>Horizontal Viewing Angle</i>	110°	110°	110°	160°
<i>Vertical Viewing Angle</i>	100°	110°	110°	120°
<i>Physical Resolution – Px/sqm</i>	62.500	27.778	10.000	6.400
<i>Brightness – NIT</i>	~1.200	~1.600	~5.100	~5.100
<i>Refresh Rate – Hz</i>	1.000	1.000	1.000	1.000
<i>Medium Consumption – Kw/sqm</i>	0,52	0,32	0,52	0,44

Note: with the horizontal and vertical numbers of the screen type panels, you can create the screen sizes, which meet your request.

ELECTRONIC CONTROL SYSTEM FOR SPORT

DLX Club-Live DLX Club DLX Club-Plus
Dia-Log System-II (PLC Diagnostic and Remote ON/OFF)

ACCESSORIES	
Spare Parts KIT	DLX Box Opto-X
DLX MT-Sport	DLX Box Opto-SX
DLX MT-CSS (Replay, Slow Motion)	DLX Box Opto-WUX
Support Structure	RJ2bnc-2 Converter
Fiber Optic	RJ2bnc-2 Converter (80m)
	RJ2bnc-2 Converter (200m)